

03IMB

Wide Multi-Deck Island Merchandiser 6', 8' & 12' (Deli / Meat) Single Wrap-Around End

ELECTRICAL DATA

Case Length	Fans Per Case	High Efficiency Fans		Anti-Condensate Heaters		Defrost Heaters			
		120 Volts		120 Volts		208 Volts		240 Volts	
		Amps	Watts	Amps	Watts	Amps	Watts	Amps	Watts
6'	4	0.31	18.4	0.63	76.0	5.77	1200	6.66	1596
8'	6	0.46	27.6	0.88	106.0	7.70	1600	8.88	2130
12'	8	0.62	36.8	1.24	149.0	11.54	2400	13.32	3200

LIGHTING DATA

Case End	Shelf Depth	Lights Per Row	Light Length	Clearvoyant LED Lighting • (Per Light Row)			
				Standard Power (Cornice or Shelf)		High Power (Cornice)	
				120 Volts		120 Volts	
				Amps	Watts	Amps	Watts
6' Single Butt	Top Sill	3	1 (2ft), 2 (4ft)	0.25	29.8	0.45	53.7
6' Single Butt	8"	3	1 (0.5ft), 2 (3ft)	0.16	18.7	0.27	32.5
6' Single Butt	10", 12", 14", 16"	3	1 (1ft), 2 (3ft)	0.16	19.6	0.29	35.2
8' Single Butt	Top Sill	5	1 (2ft), 4 (3ft)	0.33	39.2	0.59	70.3
8' Single Butt	8"	3	1 (0.5ft), 2 (5ft)	0.26	30.7	0.46	55.3
8' Single Butt	10", 12", 14", 16"	3	1 (1ft), 2 (5ft)	0.26	31.6	0.48	58.0
12' Single Butt	Top Sill	7	1 (2ft), 6 (3ft)	0.47	55.8	0.83	100.1
12' Single Butt	8"	5	1 (0.5ft), 2 (4ft), 2 (5ft)	0.45	54.5	0.82	98.3
12' Single Butt	10", 12", 14", 16"	5	1 (1ft), 2 (4ft), 2 (5ft)	0.46	55.4	0.84	101.0

GUIDELINES and CONTROL SETTINGS

Application	BTUH/ft •		Superheat Set Point @ Bulb (°F)	Evaporator (°F)	Discharge Air (°F)	Discharge Air Velocity (FPM) •
	Conventional	Parallel				
Meat	1530	1381	6 - 8	17	26	270
Deli	1409	1272	6 - 8	22	30	270

DEFROST CONTROLS

Defrosts Per Day	Run-Off Time (Min)	Electric Defrost		Timed-Off Defrost •		Hot Gas Defrost	
		Fail-Safe (Min)	Termination Temp (°F)	Fail-Safe (Min)	Termination Temp (°F)	Fail-Safe (Min)	Termination Temp (°F)
4	6 - 8	30	47	45	45	26	45

Hillphoenix

REVISION: 120501_0000

A DOVER COMPANY



All measurements are taken per ASHRAE - 72 - 2005 specifications. Hillphoenix refrigerated display cases for sale in the United States meet or exceed Department of Energy 2012 energy efficiency requirements.

Defrost Schedule	
Defrosts per Day	Time
1	12 midnight
2	12am - 12pm
3	6am - 2pm - 10pm
4	12am-6am-12pm-6pm
6	12am-4am-8am-12pm-4pm-8pm

03IMB Wide Multi-Deck Island Merchandiser

6', 8' & 12' (Deli / Meat) Single Wrap-Around End

NOTES:

- Listed LED lighting values represent a full row of shelves (including wrap-around ends).
- BTUH/ft notes:
 - Listed BTUH/ft data represent unlighted shelves. For LED lighting, add 9 BTUH/ft per row of lighted shelving. For T8 lighted shelves, see Hillphoenix Bluebook Appendix D for BTUH, amp and watt data.
 - Load data represents the sum of both coils.
- Listed discharge air velocity represents the average velocity at the peak of defrost.
- Timed-off defrost is only recommended when an enhanced efficiency coil with a 22°F evaporator is used.
- Temperature and defrost settings listed above are recommended start-up settings. Final operational settings may need to be adjusted for the store conditions in which the case operates.
- The recommended evaporator temperatures may need to be adjusted based on system setup, store conditions, etc. The minimum recommended evaporator temperature is 4°F below the listed evaporator temperature.



REVISION: 120501_0000





All measurements are taken per ASHRAE - 72 - 2005 specifications. Hillphoenix refrigerated display cases for sale in the United States meet or exceed Department of Energy 2012 energy efficiency requirements.

Defrost Schedule	
Defrosts per Day	Time
1	12 midnight
2	12am - 12pm
3	6am - 2pm - 10pm
4	12am-6am-12pm-6pm
6	12am-4am-8am-12pm-4pm-8pm

03IMB

Wide Multi-Deck Island Merchandiser 6', 8' & 12' (Deli / Meat) Single Wrap-Around End



NOTES:

* STUB-UP AREA

- FRONT AND CENTER SILL HEIGHTS VARY WITH BASEFRAME HEIGHT
- SUCTION LINE - 7/8", LIQUID LINE - 3/8"
- AVAILABLE SHELF SIZES: 10", 12", 14" & 16"
- DASHED LINES SIGNIFY AREA INSIDE BASE RAIL BEHIND KICK-PLATE

